

HIP

CMZ2208

18 Zones Detection Walkthrough



Functional Configuration

- Portable metal can be excluding
- Double sets high brightness red-green digital tube display function
- 5.7-inch LCD display / Rectangle
- Integrated four-button panel operation mode
- Multi networking interface
- Pass people statistics function
- Alarm statistics function
- Ultra-brightness patch double row regions indicator light
- 50 optional working frequency bands
- Alarm volume 0-99 adjustable
- 100 alarm sound selection modes
- Front bilateral region alarm indicator light
- The sensitivity of each detection defense zone can be adjusted
- Each zone sensitivity 0-399 adjustable
- Safety level 0-99 optional
- 18 Zones Detection
- Recover factory setting



Specifications

Model	CMZ2208
Vertical Dimension	2230 x 920 x 440mm
Vertical Aisle Dimension	2000 x 715mm
Net Weight	40KG
Gross Weight	45KG
Operating Voltage	AC90V ~ 240V 50/60Hz
Power Consumption	20W
Operating Frequency Range	1-50 Bands
Working Environmental Temp.	-20°C ~ 65°C
Installation Environment	(W) 100cm x (L) 200cm (metal-free minimum range) Sheet Transverse
Regional Detect Metal Precision Range	Maximum Sensitivity ≥ 10g Metal

ISO9001:2015

ขอสงวนสิทธิ์ในการเปลี่ยนแปลงรายละเอียดโดยไม่ต้องแจ้งให้ทราบล่วงหน้า บริษัท เอช ไอ พี โทมอล จำกัด

THE BEST
SECURITY SOLUTION

