

HIP

2MP VF Dome Network Camera



จับรายละเอียด
คมชัด...ทุกย่างก้าว
ปลอดภัย 100%



Human Body Auto Tracking

ไม่ต้องเดินสาย ติดตั้งง่าย ดูผ่านมือถือฟรี



MODEL
CMU2192

ตอบโจทย์ CCTV HIP คุณภาพ
ภาพคมชัดระดับ **Full HD**

2.0
MegaPixel

Full HD
CAMERA



FEATURES

- ▶ High quality image with 2MP, 1/2.7" CMOS sensor
- ▶ 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
- ▶ Ultra 265, H.265, H.264, MJPEG
- ▶ 120dB true WDR technology enables clear image in strong light scene
- ▶ Support 9:16 Corridor Mode
- ▶ Built-in Mic
- ▶ Smart IR, up to 40m (131ft) IR distance
- ▶ Supports 128 G Micro SD card
- ▶ IK10 vandal resistant
- ▶ IP67 protection
- ▶ Support PoE power supply
- ▶ 3-Axis

ISO9001:2015

ขอสงวนสิทธิ์ในการเปลี่ยนแปลงรายละเอียดโดยไม่ต้องแจ้งให้ทราบล่วงหน้า บริษัท เอช ไอ พี โกลบอล จำกัด

THE BEST
SECURITY SOLUTION



2MP VF Dome Network Camera

CMU2192

HIP



ใช้งานร่วมกับ Network video Record

Technical Specifications

Model	CMU2192
Camera	
Sensor	1/2.7", 2.0 megapixel, progressive scan, CMOS
Minimum Illumination	Colour: 0.005Lux (F1.6, AGC ON) 0Lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)a
Shutter	Auto/Manual, 1 - 1/100000s
S/N	>52dB
WDR	120dB
Lens	
Lens Type	2.8 ~ 12mm, AF automatic focusing and motorized zoom lens
Angle of View (H)	108.05° ~ 32.59°
Angle of View (V)	56.81° ~ 18.36°
Illuminator	
IR Range	Up to 40m (131ft) IR range
IR On/Off Control	Auto/Manual
Video	
Video Compression	Ultra 265, H.265, H.264
Resolution	Main Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps;
Video Bit Rate	128 Kbps~6144 kbps
Support	Motion Detection , Privacy Mask
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Image Setting	Image rotation, brightness, saturation, contrast, sharpness, gain adjustable by web browser
Digital noise reduction	2D/3D DNR
Smart IR	Supported
Flip	Normal/Vertical/Horizontal/180
HLC	Supported
BLC	Supported
Defog	Digital Defog
Audio	
Audio Compression	G.711
Suppression	Supported
Sampling Rate	8KHZ
Storage	
Edge Storage	Micro SD, up to 128GB
Network Storage	ANR, NAS(NFS)
Smart	
Edge Storage	Cross line, intrusion(based on human body detection) motion detection, tampering alarm, audio detection
Network Storage	Watermark, IP address filtering, access policy, ARP protection, RTSP authentication, user authentication
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS, SNMP, 802.1x, ONVIF
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+
Interface	
Network	10/100M Base-TX Ethernet
Built-in Mic	Supported
General	
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 7.5W
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Ingress Protection	IP67
Vandal Resistant	IK10



HIPGROUP



@HIPGROUP



HIP Channel



www.hip.co.th