



NETWORK VIDEO RECORD 16-Channel



4K / 5MP / 4MP / 3MP / 1080P / HD NVR

MODEL
CMU3016-H2

ตอบโจทย์เครื่องบันทึก 16 Channel
ภาพคมชัดระดับ **4K**



**ULTRA
H.265**

**16
CH**

**2
SATA**

FEATURES

- ▶ Support Ultra265/H.265/H.264 video formats
- ▶ 16-channel input
- ▶ Third-party IP cameras supported with ONVIF conformance: Profile S, Profile G, Profile T
- ▶ HDMI and VGA simultaneous output
- ▶ Up to 8 Megapixels resolution recording
- ▶ Accurate retrieval, instant playback
- ▶ 2 SATA HDDs, up to 6TB for each HDD
- ▶ ANR technology to enhance the storage reliability when the network is disconnected
- ▶ Support cloud upgrade

ISO9001:2015

ขอสงวนสิทธิ์ในการเปลี่ยนแปลงรายละเอียดโดยไม่ต้องแจ้งให้ทราบล่วงหน้า บริษัท เอช ไอ พี โกลบอล จำกัด

**THE BEST
SECURITY SOLUTION**



NETWORK VIDEO RECORD

16-Channel

Model : CMU3016-H2



ULTRA
H.265

16
CH

2
SATA



Technical Specifications

Model	CMU3016-H2
Video/Audio Input	
IP Video Input	16-ch
Two-way Audio Input	1-ch, RCA
Network	
Incoming Bandwidth	160Mbps
Outgoing Bandwidth	96Mbps
Remote Users	128
Protocols	P2P, UPnP, NTP, DHCP, PPPoE
Video/Audio Output	
HDMI/VGA Output	HDMI: 4K (3840x2160)@30, 1920x1080p@60, 1920x1080p@50, 1600x1200@60, 1280x1024@60, 1280x720@60, 1024x768@60 VGA: 1920x1080p@60, 1920x1080p@50, 1280x1024@60, 1280x720@60, 1024x768@60
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Audio Output	1-ch, RCA
Synchronous Playback	16-ch
Corridor Mode Screen	3/4/5/7/9/10/12/16
Decoding	
Decoding format	Ultra 265/H.265/H.264
Live view/Playback	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	1 x 4K@30, 1 x 6MP@30, 1 x 5MP@30, 2 x 4MP@30, 4 x 1080p@30, 8 x 720p@30, 16 x D1
Hard Disk	
SATA	2 SATA interface
Capacity	up to 6TB for each disk
Smart	
VCA Detection	Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking
VCA Search	Face search, Behavior search
Statistical Analysis	People counting
External Interface	
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface
USB Interface	Rear panel: 1 x USB2.0, Front panel: 1 x USB2.0
General	
Power Supply	12V DC Power Consumption: ≤7 W (without HDD)
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH (non-condensing)

